GENERAL NOTES AND SPECIFICATIONS

- ALL WORK SHALL CONFORM TO ALL LOCAL, STATE, AND NATIONAL CODES ALONG WITH ALL VA STANDARDS. EQUIPMENT SHALL BE INSTALLED IN ACCORDANCE WITH MANUFACTURER'S WRITTEN RECOMMENDATIONS.
- THE MECHANICAL CONTRACTOR SHALL OBTAIN AND PAY FOR ALL PERMITS, FEES, AND INSPECTIONS REQUIRED FOR HIS WORK.
- ALL MATERIALS, EQUIPMENT AND PRODUCTS INCORPORATED IN THE WORK UNDER THE CONTRACT SHALL BE NEW, OF A SUITABLE GRADE FOR THE PURPOSES INTENDED, AND TO THE EXTENT POSSIBLE, STANDARD PRODUCTS OF THE VARIOUS MANUFACTURERS EXCEPT WHERE SPECIAL CONSTRUCTION OR PERFORMANCE FEATURES ARE CALLED FOR.
- ANY EQUIPMENT OR MATERIAL DEVIATIONS FROM THAT SPECIFIED OR DETAILED ON THIS DRAWING SHALL BE SUBJECT TO THE APPROVAL OF THE ARCHITECT/ENGINEER. ALL PROPOSED EQUIPMENT DEVIATIONS SUBMITTED SHALL BE SIMILAR BOTH IN QUALITY AND CAPACITY TO
- ALL MECHANICAL EQUIPMENT SHALL BE LISTED AND LABELED BY UNDERWRITERS LABORATORIES (U.L.).
- THE MECHANICAL CONTRACTOR SHALL INSTALL EQUIPMENT AS SHOWN ON THE DRAWINGS ALLOWING FOR SUFFICIENT ACCESS AND CLEARANCE SPACE FOR EQUIPMENT MAINTENANCE, REPAIRS AND REPLACEMENT. PROVIDE PROPER CLEARANCES FOR REQUIRED PIPING AND ELECTRICAL SERVICES AND CONNECTIONS. INSTALL ALL EQUIPMENT WITH REQUIRED ACCESS AND CLEARANCES IN ACCORDANCE WITH MANUFACTURER'S WRITTEN RECOMMENDATIONS AND/OR WITH ALL APPLICABLE CODES AND STANDARDS.
- THE MECHANICAL CONTRACTOR SHALL COORDINATE THE INSTALLATION AND ROUTING OF ALL PROPOSED DUCTWORK, PIPING AND EQUIPMENT WITHIN THE BUILDING STRUCTURE.
- THE MECHANICAL CONTRACTOR SHALL PROVIDE AND INSTALL HIS OWN SUPPORT EQUIPMENT. LOCATIONS SHALL BE COORDINATED WITH ALL CONTRACTORS PRIOR TO INSTALLATION.
- THE ELECTRICAL CONTRACTOR SHALL BE RESPONSIBLE FOR ALL POWER CONNECTIONS TO THE EQUIPMENT PROVIDED UNDER THIS
- 10. THE MECHANICAL CONTRACTOR SHALL BE RESPONSIBLE FOR ALL CONTROL WIRING FOR HIS EQUIPMENT.
- DUCTWORK AND PIPING LAYOUTS AND LOCATIONS ARE SCHEMATIC. DO NOT SCALE THESE DRAWINGS. EXACT ROUTING OF DUCTWORK AND PIPING MUST BE DETERMINED IN THE FIELD. ALL DIMENSIONS SHALL BE FIELD VERIFIED BY THE CONTRACTOR BY ACTUAL MEASUREMENT AND OBSERVATION BEFORE ORDERING OR FABRICATING ANY DUCTWORK, PIPING OR EQUIPMENT. ANY DISCREPANCIES BETWEEN THE REQUIREMENTS OF THE CONTRACT DOCUMENTS AND THE EXISTING CONDITIONS OR DIMENSIONS SHALL BE REPORTED TO THE A/E AND VMAC COTR BEFORE THE PERFORMANCE OF ANY WORK. FAILURE TO VERIFY AND REPORT SHALL CONSTITUTE THE CONTRACTOR'S ACCEPTANCE OF THE EXISTING CONDITIONS AS FIT FOR THE PROPER EXECUTION OF HIS WORK. SEE ARCHITECTURAL DRAWINGS FOR FINAL LOCATION OF CEILING INSTALLED.
- DUCTWORK AND PIPING SHALL BE KEPT AS CLOSE AND HIGH AS POSSIBLE TO THE BUILDING WALLS, CEILING AND FLOOR AND ROOF STRUCTURE IN ORDER THAT THE MAXIMUM AMOUNT OF SPACE IS AVAILABLE. ADDITIONAL OFFSETS, FITTINGS, ETC. NOT SHOWN BUT REQUIRED TO MAINTAIN MAXIMUM CLEARANCE SHALL BE PROVIDED AT NO ADDITIONAL COST,
- THE MECHANICAL CONTRACTOR SHALL BE RESPONSIBLE FOR ALL PATCHING, PAINTING AND CLEANING ASSOCIATED WITH THIS PROJECT UNLESS NOTED OTHERWISE.
- 14. PROVIDE A COMPLETE 1-YEAR WARRANTY ON ALL LABOR AND MATERIALS.

one eignin inch = one foot

0 4 8 16

- CONTRACTOR SHALL FURNISH A BOUND SET OF OPERATING AND MAINTENANCE INSTRUCTIONS FOR ALL EQUIPMENT TO THE OWNER UPON
- 16. INSTALL ESCUTCHEONS IN ALL PLACES WHERE PIPING PENETRATES A WALL IN AN EXPOSED LOCATION.
- THE MECHANICAL CONTRACTOR SHALL MAKE A COMPLETE REVIEW OF THE MECHANICAL PLANS, INCLUDING THE SCHEDULES AND DETAILS PRIOR TO INSTALLATION OF ANY MECHANICAL SYSTEMS AND SHALL RESOLVE ANY CONFLICTS WITH THE ENGINEER.
- 18. CONTRACTOR SHALL TAKE POSSESSION OF AND DISPOSE OF ALL EXISTING MATERIALS AND EQUIPMENT BEING DEMOLISHED AND/OR REMOVED. ALL ITEMS SHALL BE DISPOSED OF IN FULL COMPLIANCE WITH ALL APPLICABLE LAWS, RULES, AND REGULATIONS THAT APPLY. CONTRACTOR IS RESPONSIBLE FOR ALL COSTS ASSOCIATED WITH THE DISPOSAL.
- 19. INSTALL SHUTOFF-DUTY VALVES AT EACH BRANCH CONNECTION TO SUPPLY MAINS, AND AT SUPPLY CONNECTION TO EACH PIECE OF EQUIPMENT. INSTALL CHECK VALVES AT EACH PUMP DISCHARGE AND ELSEWHERE AS REQUIRED TO CONTROL FLOW DIRECTION.
- DRAWING PLANS, SCHEMATICS, AND DIAGRAMS INDICATE GENERAL LOCATION AND ARRANGEMENT OF PIPING SYSTEMS. INSTALL PIPING INDICATED TO BE EXPOSED AND PIPING IN EQUIPMENT ROOMS AND SERVICE AREAS AT RIGHT ANGLES OR PARALLEL TO BUILDING WALLS. DIAGONAL RUNS ARE PROHIBITED UNLESS SPECIFICALLY INDICATED OTHERWISE. INSTALL PIPING FREE OF SAGS AND BENDS. INSTALL PIPING TO ALLOW APPLICATION OF INSULATION
- REAM ENDS OF PIPES AND TUBES AND REMOVE BURRS. BEVEL PLAIN ENDS OF STEEL PIPE. REMOVE SCALE, SLAG, DIRT, AND DEBRIS FROM INSIDE AND OUTSIDE OF PIPE AND FITTINGS BEFORE ASSEMBLY.
- THREADED JOINTS: THREAD PIPE WITH TAPERED PIPE THREADS ACCORDING TO ASME B1.20.1. CUT THREADS FULL AND CLEAN USING SHARP DIES. REAM THREADED PIPE ENDS TO REMOVE BURRS AND RESTORE FULL ID. JOIN PIPE FITTINGS AND VALVES AS FOLLOWS: APPLY APPROPRIATE TAPE OR THREAD COMPOUND TO EXTERNAL PIPE THREADS UNLESS DRY SEAL THREADING IS SPECIFIED. DAMAGED THREADS: DO NOT USE PIPE OR PIPE FITTINGS WITH THREADS THAT ARE CORRODED OR DAMAGED. DO NOT USE PIPE SECTIONS THAT
- INSTALL MANUAL AIR VENTS AT HIGH POINTS IN PIPING, AT HEAT-TRANSFER COILS, AND ELSEWHERE AS REQUIRED FOR SYSTEM AIR
- CUT INSULATION IN A MANNER TO AVOID COMPRESSING INSULATION MORE THAN 75 PERCENT OF ITS NOMINAL THICKNESS. FINISH INSTALLATION WITH SYSTEMS AT OPERATING CONDITIONS. REPAIR JOINT SEPARATIONS AND CRACKING DUE TO THERMAL MOVEMENT. REPAIR DAMAGED INSULATION FACINGS BY APPLYING SAME FACING MATERIAL OVER DAMAGED AREAS. EXTEND PATCHES AT LEAST 4 INCHES BEYOND DAMAGED AREAS. ADHERE, STAPLE, AND SEAL PATCHES SIMILAR TO BUTT JOINTS.
- 25. INSULATE INSTRUMENT CONNECTIONS FOR THERMOMETERS, PRESSURE GAGES, PRESSURE TEMPERATURE TAPS, TEST CONNECTIONS, FLOW METERS, SENSORS, SWITCHES, AND TRANSMITTERS ON INSULATED PIPES, VESSELS, AND EQUIPMENT. SHAPE INSULATION AT THESE CONNECTIONS BY TAPERING IT TO AND AROUND THE CONNECTION WITH INSULATING CEMENT AND FINISH WITH FINISHING CEMENT,
- THE MECHANICAL CONTRACTOR SHALL TAKE THE LEAD IN PREPARATION OF COORDINATION DRAWINGS. SUCH DRAWINGS SHALL BE COMPLETED WITH COORDINATION FROM THE GENERAL CONTRACTOR AND ALL OTHER MAJOR AND MINOR SUBCONTRACTORS. PROVIDE PLAN VIEWS, SECTIONS AND ELEVATIONS, AS REQUIRED, TO FULLY COORDINATE ALL NEW WORK WITH ITSELF AND EXISTING CONDITIONS. DRAWINGS SHALL SHOW, BUT NOT BE LIMITED TO, ALL DUCTWORK, AIR DISTRIBUTION, MECHANICAL EQUIPMENT, MECHANICAL PIPING, FIRE PROTECTION PIPING, PLUMBING PIPING, CABLE TRAYS, LIGHTING FIXTURES, CEILING GRID AND HEIGHT, BEAMS AND JOISTS (WITH ELEVATIONS MARKED), ELECTRICAL CONDUIT LARGER THAN 2 INCHES IN DIAMETER AND ANY OTHER CEILING MOUNT DEVICES OR EQUIPMENT THAT PROTRUDE INTO THE CEILING CAVITY. IF THERE ARE ANY OUTSTANDING ISSUES THAT CANNOT BE RESOLVED, CONSULT WITH ARCHITECT AND/OR ENGINEER (THROUGH THE VA COTR) FOR GUIDANCE AND MAKE CORRECTIONS IN ACCORDANCE WITH DIRECTIONS GIVEN. IT IS IMPORTANT TO NOTE THAT FABRICATION CANNOT BEGIN UNTIL COORDINATION DRAWINGS HAVE BEEN APPROVED. ANY INSTALLATION COMMENCED PRIOR TO APPROVAL IS TAKEN AT THE CONTRACTORS OWN RISK AND MAY HAVE TO BE MODIFIED, MOVED AND/OR RECONFIGURED AT CONTRACTORS COST.

ALTERNATES

Add Alternate #1:

Construction and fit out of therapy pool, mechanical area (1-606), pool enclosure (1-603), associated roofing, specialty equipment housed within the pool area, doors 600B, 603, 604B, and sidelight 604 are all alternate. Base bid to include demolition of mechanical unit, slab, and fence (D8); demolition of concrete ramp and canopy (D2, D7, D11); demolition of exterior door near column G4 and subsequent infill of exterior wall.

Plumbing sheets: PP101, PP111, PP112, PP113, PP301, PP302, and PP601 (all plumbing work related to therapy pool)

Mechanical sheets: MH111, MH401, MH503, MH504, MP101, MP111, and MH602 (all mechanical work related to therapy pool) Electrical sheets: ED101, E-102, E-103, E-104, E-105, E-601, E603, and FA102 (all electrical work related to therapy pool)

A/E	ARCHITECT / ENGINEER	D	DAMPER - AUTOMATIC	HD	HOOD	MH	MANHOLE	SD	SUPPLY AIR DIFFUSER
AAHX	AIR TO AIR HEAT EXCHANGER	D-1	OUTDOOR AIR DAMPER	HOA	HAND/OFF/AUTOMATIC	MHP	MOTOR HORSEPOWER	SDPR	SMOKE DAMPER
AB	AIR BLENDER	D-2	RETURN AIR DAMPER	HP	HEAT PUMP	MIN	MINIMUM	SDR	SMOKE DAMPER (RETURN)
AAV	AUTOMATIC AIR VENT	D-3	RELIEF AIR DAMPER	HP HPDT	HORSEPOWER HIGH PRESSURE DRIP TRAP	MM	MILLIMETER	SDS SEN	SMOKE DAMPER (SUPPLY)
ACC ACCH	AIR COOLED CONDENSER AIR COOLED CHILLER	DB Db	DECIBELS DRY-BULB TEMPERATURE	HPD1 HPR	HIGH PRESSURE DRIP TRAP HIGH PRESSURE RETURN (STEAM	MOV MPR	MOTOR OPERATED VALVE MEDIUM PRESSURE RETURN (STEAM	SEN SF	SENSIBLE HEAT SUPPLY FAN
ACCU	AIR-COOLED CONDENSING UNIT	DDC	DIRECT DIGITAL CONTROLS	HEIX	CONDENSATE)	IVIFIX	CONDENSATE)	SG	SUPPLY AIR GRILLE
ACU	AIR CONDITIONING UNIT	DEG	DEGREE	HPS	HIGH PRESSURE SUPPLY (STEAM)	MPS	MEDIUM PRESSURE STEAM	SH	STEAM HUMIDIFIER
ACD	AUTOMATIC CONTROL	DF	DIFFUSER	HRC	HEAT RECOVERY COIL	MRI	MAGNETIC RESONANCE IMAGING	SHC	STEAM HEATING COIL
	DAMPER,MODULATING	DIA	DIAMETER	HRD	HEAT RECOVERY DEVICE	MTD	MEAN TEMPERATURE DIFFERENCE	SI	SQUARE INCHES
ACD-TP	AUTOMATIC CONTROL DAMPER,TWO	DIW	DEIONIZED WATER	HRP	HYDRONIC RADIANT (CEILING) PANEL	MVD	MANUAL VOLUME DAMPER	SP	STATIC PRESSURE
AD	POSITION	DP	DEW POINT TEMPERATURE DIFFUSER PLATE	HRW	HEAT RECOVERY WHEEL HUMIDISTAT	MZ	MULTI-ZONE	SP GR SPD	SPECIFIC GRAVITY
AD AF	ACCESS DOOR AFTER FILTER	DP DPA	DIFFERENTIAL PRESSURE ASSEMBLY	HSTAT HTM	HUMIDIFIER TERMINAL	NA	NOT APPLICABLE	SPRV	SUPPLY PROCESS AND DISTRIBUTION STEAM PRESSURE REDUCING VALVE
AFCV	AFTER FILTER AIR FLOW CONTROL VALVE	DPS	DIFFERENTIAL PRESSURE SENSOR	HUM	HUMIDIFIER UNIT MOUNTED	NC NC	NOISE CRITERIA	SPS	STATIC PRESSURE SENSOR
AFF	ABOVE FINISHED FLOOR	DX	DIRECT EXPANSION	HVU	HEATING AND VENTILATING UNIT	NC	NORMALLY CLOSED	SQ FT	SQUARE FOOT (FEET)
AFMD	AIR FLOW MEASURING DEVICE	DXCC	DIRECT EXPANSION COOLING COIL	HW	HOT WATER	NG	NATURAL GAS	SR	SUPPLY AIR REGISTER
AFW	AIR FOIL WHEEL (FAN)			HWC	HOT WATER COIL	NGFM	NATURAL GAS FLOWMETER	SS	STAINLESS STEEL
AHU	AIR-HANDLING UNIT	EA	EXHAUST AIR	HWHC	HOT WATER HEATING COIL	NO	NORMALLY OPEN	SSHX	STEAM TO STEAM HEAT EXCHANGER
AMP	AMPERGE	EAT	ENTERING AIR TEMPERATURE	HWP	HEATING HOT WATER PUMP	NOAA	NATIONAL OCEANIC & ATMOSPHERIC	SSR	SOLID SEPARATOR
AP APD	ACCESS PANEL AIR PRESSURE DROP	EC ECC	EVAPORATIVE COOLER ENGINEERING CONTROL CENTER	HWR HWS	HEATING HOT WATER RETURN HEATING HOT WATER SUPPLY	NOM	ADMINISTRATION NOMINAL	ST SUH	STEAM TRAP STEAM UNIT HEATER
ARI	AIR CONDITIONING AND	ECU	EVAPORATIVE CONDENSER UNIT	HWUH	HOT WATER UNIT HEATER	NPLV	NON-STANDARD PART LOAD VALUE	SV	STEAM PRESSURE REDUCING VALVE
74141	REFRIGERATION INSTITUTE	EDH	ELECTRIC DUCT HEATER	HVD	HOISTWAY VENT DAMPER	NPSH	NET POSITIVE SUCTION HEAD	SVS	STEAM VENT SILENCER
AS	AIR SEPARATOR	EER	ENERGY EFFICIENCY RATIO	HX	HEAT EXCHANGER	NTS	NOT TO SCALE	SWHX	STEAM TO WATER HEAT EXCHANGER
ASME	AMERICAN SOCIETY OF MECHANICAL	EF	EXHAUST FAN	HZ	HERTZ				
	ENGINEERS	EG	EXHAUST GRILLE		W.D. 17(0)::-	OA	OUTSIDE AIR	T & PCV	TEMPERATURE AND PRESSURE
AW	AIR WASHER	EGS	EMERGENCY GAS SHUTOFF	I/O	INPUT/OUTPUT	OAG	OUTSIDE AIR GRILLE	TAD	CONTROL VALVE
AXF	AXIAL FLOW	EGT EH	ENTERING GLYCOL TEMPERATURE EXHAUST HOOD	IAQ IBT	INDOOR AIR QUALITY INVERTED BUCKET TRAP	OAI OD	OUTSIDE AIR INTAKE OUTSIDE DIAMETER	TAB TD	TESTING, ADJUSTING, BALANCE TEMPERATURE DIFFERENCE
В	BOILER	EH EJ	EXHAUST HOOD EXPANSION JOINT	ICF	INVERTED BUCKET TRAP IN-LINE CENTRIFUGAL FAN	OD OFM	OIL FLOWMETER	TDH	TOTAL DYNAMIC HEAD
BD	BUTTERFLY DAMPER	EMD	END OF MAIN DRIP (STEAM)	ICU	INTENSIVE CARE UNIT	OF IVI	OPERATING ROOM	TDS	TOTAL DYNAMIC HEAD TOTAL DISSOLVED SOLIDS
BDD	BACKDRAFT DAMPER	ENT	ENTERING	ID	INSIDE DIAMETER	 ·		TG	TRANSFER GRILLE
BDR	BASE BOARD RADIATOR	ER	EXHAUST REGISTER	IFB	INTEGRAL FACE AND BYPASS	Р	PUMP	TP	TRAP
BFP	BACKFLOW PREVENTER	ERC	ELECTRIC REHEAT COIL	IN	INCHES	PA	PASCAL	TR	TOP REGISTER
BFT	BOILER PLANT FIRE TUBE	ERP	ELECTRIC RADIANT PANEL	IN HG	INCHES OF MERCURY	PC	PUMPED CONDENSATE	TSP	TOTAL STATIC PRESSURE
BG BHP	BOTTOM GRILLE BRAKE HORSEPOWER	ESP ET	EXTERNAL STATIC PRESSURE EXPANSION TANK	IN WC IN WG	INCH WATER COLUMN INCH WATER GAUGE	PCF PD	POUNDS PER CUBIC FOOT (FEET) PRESSURE DROP	TSTAT	THERMOSTAT TERMINAL UNIT
BHW	HOT WATER HEATING BOILER	ETO	ETHYLENE OXIDE	IN WG IN-LB	INCH WATER GAUGE INCH-POUND	PEF	PROPELLER (TYPE) EXHAUST FAN	TU TWU	THRU-WALL UNIT
BHX	BOILER BLOWDOWN HEAT	EUH	ELECTRIC UNIT HEATER	IPLV	INTERGRATED PART LOAD VALUE	PF	PRE-FILTER	1440	THING-WALL OINT
51.17	EXCHANGER	EWC	EVAPORATIVE WATER COOLER	IRH	INTRARED HEATER	PG	PRESSURE GAGE	UC	UNDER CUT
BIW	BACKWARD INCLINED WHEEL (FAN)	EWT	ENTERING WATER TEMPERATURE	IS	INSECT SCREEN	PGW	PROPYLENE GLYCOL-WATER	UC	UNIT COOLER
BMT	BONE MARROW TRANSPLANT	EX.	EXISTING	IU	INDUCTION UNIT		(SOLUTION)	UH	UNIT HEATER
BR	BOTTOM REGISTER	_		IV	INLET VANES	PHC	PREHEAT COIL	UL	UNDERWRITERS LABORATORY
BSC	BIOLOGICAL SAFETY CABINETS BLOWOFF TANK	F F&T	FAHRENHEIT FLOAT AND THERMOSTATIC	l.a.	KILOGRAM	PPM PRS	PARTS PER MILLION PRESSURE REGULATING (VALVE)	URV	UPBLAST UNIT VENTILATOR
BT BTC	BLOWOFF TANK BLOWOFF TANK CONTROL VALVE	F/SDPR	COMBINATION FIRE SMOKE DAMPER	kg kg/HR	KILOGRAM KILOGRAM PER HOUR	PKS	STATION	V	VALVE
BTU	BRITISH THERMAL UNIT	FA	FREE AREA	kPa	KILOPASCAL	PRV	PRESSURE REGULATING VALVE	VAF	VANE-AXIAL FAN
BTUH	BRITISH THERMAL UNIT PER HOUR	FC	FLEXIBLE CONNECTION	kW	KILOWATT	PSI	POUNDS PER SQUARE INCH	VAV	VARIABLE AIR VOLUME
BWT	BOILER PLANT WATER TUBE	FCU	FAN COIL UNIT (4 PIPE)	kWh	KILOWATT HOUR	PSIA	POUNDS PER SQUARE INCH –	VD	VOLUME DAMPER (MANUAL OPPOSED
	05117100105 (051 01110)	FCUC	FAN COIL UNIT COOLING ONLY			2010	ABSOLUTE		BLADE)
C	CENTIGRADE (CELCIUS)	FCUH	FAN COIL UNIT HEATING ONLY	L . //-	LITER	PSIG	POUNDS PER SQUARE INCH – GAGE	VFD	VARIABLE FREQUENCY DRIVE
CC CCD	COOLING COIL COOLING COIL CONDENSATE DRAIN	FCW FD	FORWARD CURVED WHEEL (FAN) FLOOR DRAIN	L/h L/m	LITERS PER HOUR LITERS PER MINUTE	PSS PSV	PRIMARY SECONDARY SYSTEM PRESSURE SAFETY VALVE	VHA VI	VETERANS HEALTH ADMINISTRATION VIBRATION ISOLATOR
CD	CEILING DIFFUSER	FD FD	FIRE DAMPER	L/s	LITERS PER MINOTE LITERS PER SECOND	PTAC	PACKAGED TERMINAL AIR	VIV	VARIABLE INLET VANES
CENT	CENTRIFICAL	FF	FINAL FILTER	LAT	LEAVING AIR TEMPERATURE		CONDITIONER	VP	VACUUM PUMP
CFH	CUBIC FEET PER HOUR	FHX	FLUE GAS/FEEDWATER HEAT	LBS/HR	POUNDS PER HOUR			VPS	VARIABLE PRIMARY SYSTEM
CFM	CUBIC FEET PER MINUTE		EXCHANGER	LF	LINEAR FOOT (FEET)	R/E	RETURN OR EXHAUST	VR	VACUUM (STEAM CONDENSATE)
CFT	CUBIC FEET	FM	FLOW METER	LGT	LEAVING GLYCOL TÉMPERATURE	RA	RETURN AIR		RETURN
CFP	CHEMICAL FEED PUMP	FOP	FUEL OIL PUMP	LH	LATENT HEAT	RAD RAF	REFRIGERANT AIR DRYER	VSD	VARIABLE SPEED DRIVE
CG CH	CEILING GRILLE CHILLER	FOT FOHX	FUEL OIL TANK FUEL OIL HEAT EXCHANGER	LPG LPR	LIQUID PROPANE GAS LOW PRESSURE RETURN (STEAM	RAF RAHX	RADIO FREQUENCY ROTARY AIR HEAT EXCHANGER	VUH	VERTICAL UNIT HEATER
CHP	CHILLED WATER PUMP	FPM	FEET PER MINUTE	Li 1X	CONDENSATE)	RAT	RETURN AIR TEMPERATURE	W	WATTS
CHW	CHILLER WATER	FPS	FEET PER SECOND	LPRC	LOW PRESSURE STEAM RETURN	RCCH	REMOTE CONDENSER CHILLER	WAG	WASTE ANETHESIA GAS
CHR	CHILLED WATER RETURN	FPTU	FAN POWERED TERMINAL UNIT		(CLEAN)	RCU	RECIPROCATING CHILLER UNIT	Wb	WET-BULB (TEMPERATURE)
CHS	CHILLED WATER SUPPLY	FR	FLOOR REGISTER	LLHX	LIQUID TO LIQUID HEAT EXCHANGER	RD	REFRIGERANT DISCHARGE	WC	WATER COOLED
CI	CAST IRON	FRP	FIBER REINFORCED POLYESTER	LPS	LOW PRESSURE STEAM	RDS	ROOM DATA SHEETS	WCCH	WATER COOLED CHILLER
CM	CARBON MONOXIDE CUBIC METER	FS FSTAT	FLOW SWITCH FREEZESTAT	LPSC	LOW PRESSURE STEAM (CLEAN)	REA	RELIEF AIR RETURN FAN	WCCU WCHP	WATER COOLED HEAT BLIMBS
CM CM/S	CUBIC METER CUBIC METER PER SECOND	FSTAT	FEET	LSD LTCP	LINEAR SLOT DIFFUSER LOCAL TEMPERATURE CONTROL	RF RG	RETURN FAN RETURN GRILLE	WCHP	WATER COOLED HEAT PUMPS WATER COOLED PACKAGED UNIT
CO CO	CLEAN OUT	FT-LB	FOOT-POUND	L101	PANEL	RH	RELATIVE HUMIDITY	WEF	WALL EXHAUST FAN
CO2	CARBON DIOXODE	FTR	FIN TUBE RADIATION	LVG	LEAVING	RHC	REHEAT COIL	WF	WATER FILTER
COMP	COMPRESSOR UNIT	FV	FACE VELOCITY	LVR	LOUVER	RHG	REFRIGERANT HOT GAS	WFCV	WATER FLOW CONTROL VALVE
COP	COEFFICIENT OF PERFORMANCE	. .	0.41105	LWT	LEAVING WATER TEMPERATURE	RL	REFRIGERANT LIQUID LINE	WFM	WATER FLOWMETER
CP CB	CONDENSATE PUMP CEILING REGISTER	GA	GAUGE GALLONS	N //	METED CLUMT	RLA	RUN LOAD AMPERE REVERSE OSMOSIS	WFMD WG	WATER CACE
CR CS	CEILING REGISTER CONDENSATE STORAGE TANK	GAL GH	GALLONS GRAVITY HOOD	M M/s	METER, SI UNIT METERS PER SECOND (OR	RO RPM	REVERSE OSMOSIS REVOLUTIONS PER MINUTE	WG WPD	WATER GAGE WATER SIDE PRESSURE DROP
CSG	CLEAN STEAM GENERATOR	GPD	GALLONS PER DAY	IVI/5	METERS PER SECOND (OR METERS/SECOND)	RPIVI RR	RETURN REGISTER	VVFU	WATER SIDE FRESSURE DRUP
CT	COOLING TOWER	GPH	GALLONS PER HOUR	MA	MIXED AIR	RS	REFRIGERANT SUCTION	YR	YEAR
CU	CONDENSING UNIT	GPM	GALLONS PER MINUTE	MAT	MIXED AIR TEMPERATURE	RTU	ROOF TOP UNIT	•	
CUH	CABINET UNIT HEATER	GPR	GAS PRESSURE REGULATOR	MAU	MAKE-UP AIR UNIT	RV	RELIEF VALVE		
CV	CONSTANT VOLUME	GS	GALVANIZED STEEL	MAV	MANUAL AIR VENT	SA	SUPPLY AIR		
CW	COLD WATER (POTABLE)		LILINAIDIEED	MAX	MAXIMUM	SAD	SOUND ATTENUATING DEVICE		
CWCC	CHILLED WATER COOLING COIL	H	HUMIDIFER	MB MBH	MIXING BOX	SAT	SUPPLY AIR TEMPERATURE		
CWP CWR	CONDENSER WATER PUMP CONDENSER WATER RETURN (TO	H&CW HAC	HOT & COLD WATER HOUSEKEEPING AID CLOSET	MBH MCA	1000 BTUH MINIMUM BRANCH CIRCUIT AMPACITY	SC SCFM	SHADING COEFFICIENT STANDARD CUBIC FEET PER MINUTE		
OVVIN	COOLING TOWER)	HAC HB	HOSE BIBB	MER	MECHANICAL EQUIPMENT ROOM	SCI	SPINAL CODE INJURY		
CWS	CONDENSER WATER SUPPLY (FROM	HC	HEATING COIL	MERV	MINIMUM EFFICIENCY REPORTING	SCR	SILICON CONTROLLED RECTIFIER		
-	COOLING TOWER)	HD	HEAD		VALUE	SD	SMOKE DETECTOR		

ABBREVIATIONS

MECHANICAL LEGEND											
	CARBON DIOXIDE THERMOSTAT		VANED ELBOW (PROVIDE ALL SQUARE OR RECTANGULAR ELBOWS WITH VANES EVEN IF SYMBOL IS MISSING)	├──HPS────	HIGH PRESSURE STEAM PIPING MEDIUM PRESSURE STEAM PIPING	© -∻	MOTORIZED CONTROL VALVE STEAM TRAP				
<u>↑</u> ►	SUPPLY DIFFUSER		VANED ELBOW (SHORT RADIUS)	\\text{LPS\}	LOW PRESSURE STEAM PIPING CONDENSATE RETURN PIPING	8	PRESSURE REDUCING VALVE				
† 1 1 1 1 1 1 1 1 1 1	RETURN DIFFUSER/GRILL		STANDARD RADIUS ELBOW (LONG RADIUS)		UNKNOWN EXISTING PIPING VACUUM PIPING CHILLED WATER SUPPLY PIPING						
<u></u> †		Z 10x8 Z	NEW DUCT (INSIDE DIMENSIONS: WIDTH X DEPTH)	— CWS — → — CWR — → — HWS — →	CHILLED WATER RETURN PIPING						
<u> </u>	EXHAUST GRILL		EXISTING DUCT TO REMAIN	— HWS—— — HWR — →	HOT WATER SUPPLY PIPING HOT WATER RETURN PIPING						
H++4	ROUND FLEX DUCT		EXISTING DUCT TO BE REMOVED	⊱—FTHWS——	FIN TUBE HEATING HOT WATER SUPPLY PIPING						
	DIFFUSER TAGDIFFUSER CFM		DUCT TRANSITION		FIN TUBE HEATING HOT WATER RETURN PIPING PIPE UP						
1	LINEAR SLOT DIFFUSER		—— SIDE MOUNTED GRILLE	£	PIPE DOWN BOTTOM CONNECTION						
	BALANCING DAMPER (RECTANGULAR)				TOP CONNECTION						
<u>'</u> 	BALANCING DAMPER (ROUND)			, ,							
	FIRE DAMPER	45° SUPPLY	STANDARD BRANCH SUPPLY OR RETURN, NO SPLITTER (45° TAP)	> ✓	CAPPED OUTLET GLOBE VALVE						
	SMOKE DAMPER			\bowtie	GATE VALVE						
► R Z	INCLINED RISE, IN DIRECTION OF AIRFLOW	45° RETURN		吃 …	BALL VALVE PRESSURE RELIEF VALVE						
- D /	INCLINED DROP, IN DIRECTION OF AIRFLOW			Z	CHECK VALVE						
			ON SUPPLY DUCT (UP & DOWN)	×	PRESSURE REGULATING VALVE						
\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	CONNECT NEW DUCT TO EXISTING		ON EXHAUST DUCT (UP & DOWN)	\triangleright	WYE STRAINER VALVE						
	LIMIT OF DEMOLITION		ON RETURN DUCT (UP & DOWN)	M	BALANCING VALVE						

HVAC DESIGN DATA											
		SUMMER	2		WINTER						
		WET BULB			DEWPOINT	%	LOWEST AVERAG				
DESIGN CONDITIONS	TEMP	TEMP	% HUMIDITY	TEMP	TEMP	HUMIDITY	ANNUAL DEWPOIN				
						ı					
OUTDOOR DESIGN CONDITIONS	91 °F	75 °F	48	13 °F	-4 °F		-3 °F				
OFFICE	75 °F	68 °F	60	70 °F	28 °F	20					
CORRIDORS	75 °F	68 °F	60	70 °F	28 °F	20					
CLEAN UTILITY / STORAGE ROOM				70 °F							
LOCKER ROOM (WITH TOILET)	75 °F	68 °F	60	70 °F	28 °F	20					
TOILETS - PUBLIC (INTERIOR)	75 °F	68 °F		70 °F	28 °F	20					
HOUSEKEEPING AID CLOSET				70 °F							
CONFERENCE ROOM	75 °F	68 °F	60	70 °F	28 °F	20					
EXAM ROOMS	75 °F	68 °F	60	70 °F	28 °F	20					
LOUNGE BREAK	75 °F	68 °F	60	70 °F							
THERAPY	75 °F	68 °F	60	70 °F	28 °F	20					
VESTIBULE				50 °F							

FULLY SPRINKLERED ISSUED FOR BID

]]]		CONSULTANTS:									PROJECT MANAGER: Project Number 3627 As indicated			Drawing Title MECHANICAL NOTES, ABBREVIATIONS, AND	Project Title RENOVATE BUILDING 69		VA Project Number 542-CSI-203	
		Project Manager	Architect	Structural Engineer	MEP/FP Engineer	Civil Engineer	Fire Protection Consultant	Cost Estimator	Aquatic Consultant	Associate Architects	Draw -			LEGENDS			Building Number	Office of
		BRAY MO		- ,		GUIDON DESIGN		BRAY MOONEY		W. COOK	Bray						69	Facilities
]		CONSULT		CONSULTING	CONSULTING		GROUP	CONSULTING	AQUATIC	ARCHITECTS	N 4			Approved: Project Director	Location		Drawing Number	Management
]			SOLUTIONS	ENGINEERS	GROUP				ENGINEERING		Mooney				1400 Black Horse	Hill, Coatesville, PA		
]		410 E. 21 STREI CHESTER, PA, Tel (610) 872-3	T 2520 RENAISSANCE BLVD., 9013 SUITE 110	P.O. BOX 24 40 LITTLE ROAD	7330 CHAPEL HILL ROAD SUITE 202	, 2453 N DELAWARE STREET INDIANAPOLIS, IN 46205	7508 E. INDEPENDENCE BLVD., SUITE 116	410 E. 21 STREET CHESTER, PA, 19013	1823 DEEP RUN ROAD PIPERSVILLE, PA, 18947	1251 ROMANSVILLE ROAD COATESVILLE, PA, 19320						necked Drawn	M-001	
] 7		Tel (610) 872-3	16 KING OF PRUSSIA, PA, 19406 Tel (610) 270-0599	ZIEGLERVILLE, PA, 19492 Tel (610) 287-3194	SUITE 202 RALEIGH, NC, 27606 Tel (919) 858-7420	Tel (317) 800-6388	CHARLOTTE, NC, 28277 Tel (704) 531-9077	Tel (610) 872-3716	Tel (215) 766-0409	Tel (610) 383-4460	Consulting					D ID	D	Department of Weterspa Affairs
]	Revisions	Date	(/	- ()	(= -,		(1 , 201 201)				000				1/22/2014	DJK ORD	Dwg. 4∠ of 86	__\ veterans Atitairs

3 4 5